

## Ethylene Propylene Rubber

KUMHO POLYCHEM

### Product Data Sheet

Product Description	Features
KEP070P is an EPM rubber with narrow molecular weight distribution, high ethylene contents, When blended with polypropylene it can be used to injection molding, films, Sheets and polyolefin modifiers.	<ul style="list-style-type: none"><li>- High MFR/ High impact resistance</li><li>- Improve crack resistance, temperature flexibility, weather resistance in the modification of polyolefin thermoplastics</li></ul>

Test items	Sale Specifications	Unit	Test Method
Volatile Matter	Max 0.20	wt %	ASTM D5668
Mooney Viscosity ML(1+4)@100 °C	69.0 ± 5.0	MU	ASTM D1646
Ethylene Contents	70.5 ± 3.0	wt %	ASTM D3900

### Other Products Features

<b>Product Form</b>	Pellet
<b>Packaging</b>	25 kg/Bag in Mesh Box, 500 kg(25 kg × 20)
<b>Shelf Life</b>	24 months from date of production at room temperature in dry condition, exposure to light has to be avoided
<b>The Others</b>	RoHS Free

### Contact Information

<b>Head Office</b>	8F, East Wing, Signature Tower, #100 Cheonggyecheon-ro, Jung-gu, Seoul, Korea 82-2-6961-0000
<b>Plant</b>	613 Sandanjungang-ro, Yeosu, Jeonnam, Korea 82-61-688-2822
<b>Revision Date</b>	12/02/2020
<b>Revision No.</b>	10