

Ethylene Propylene Diene Terpolymer

KUMHO POLYCHEM

Product Data Sheet

Product Description	Features
KEP650L is an EPDM rubber with Medium molecular weight distribution, low ethylene content, high medium ENB content. It can be used to Sponges, window seals, and industrial parts.	<ul style="list-style-type: none">- Ultra fast vulcanization speed- Excellent Processability- Especially suitable for sponge applications

Test items	Sale Specifications	Unit	Test Method
Volatile Matter	Max 0.75	wt %	ASTM D5668
Mooney Viscosity ML(1+4)@125 °C	41.0 ± 5.0	MU	ASTM D1646
Ethylene Contents	59.0 ± 3.0	wt %	ASTM D3900
ENB Contents	8.7 ± 1.0	wt %	ASTM D6047

Other Products Features

Product Form	Bale
Packaging	25 kg/Bag Mesh Box, LDPE Film 900kg(25 kg × 36)
Shelf Life	24 months from date of production at room temperature in dry condition, exposure to light has to be avoided
The Others	RoHS Free

Contact Information

Head Office	8F, East Wing, Signature Tower, #100 Cheonggyecheon-ro, Jung-gu, Seoul, Korea 82-2-6961-0000
Plant	613 Sandanjungang-ro, Yeosu, Jeonnam, Korea 82-61-688-2822
Revision Date	05/01/2016
Revision No.	3